



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	CN INITIAL RELEASE	01/09/2024	BZHANG	WLI



P1
SHIELDED RJ45 MODULAR PLUG
GOLD PLATED CONTACTS
(8P8C)

P2
SHIELDED RJ45 MODULAR PLUG
GOLD PLATED CONTACTS
(8P8C)




PART NUMBER	LENGTH METERS[FEET]
TRD815SRA6BLK-0.5M	0.5[1.64]
TRD815SRA6BLK-0.7M	0.7[2.30]
TRD815SRA6BLK-1M	1.0[3.28]
TRD815SRA6BLK-1.5M	1.5[4.92]
TRD815SRA6BLK-2M	2.0[6.56]
TRD815SRA6BLK-2.5M	2.5[8.20]
TRD815SRA6BLK-3M	3.0[9.84]
TRD815SRA6BLK-5M	5.0[16.40]
TRD815SRA6BLK-7M	7.0[22.97]
TRD815SRA6BLK-10M	10.0[32.81]

NOTES:

1. PLUG CONFORMS TO TIA-1096
2. OPERATING TEMPERATURE RANGE: -10°C TO +75°C
3. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]		APPROVALS		DATE		 an INFINIT™ brand 50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936	
OVERALL CABLE LENGTH TOLERANCE:		DRAWN BY BZHANG		01/05/2024			
≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0		CHECKED BY WLI		01/05/2024			
		APPROVED BY WLI		01/05/2024			
ALL OTHER DIMENSIONAL TOLERANCES:		CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION		TELECOM/MODULAR	
.X = ± .2 [5] .XX = ± .02 [5] .XXX = ± .005 [13]		FRACTIONS ± 1/32 ANGLES ± 1°		C5E PVC FTP STR-LFT BLK			
THIRD-ANGLE PROJECTION		COLOR VARIATIONS MAY OCCUR		SIZE A	CAGE CODE 43321	ITEM NO. TRD815SRA6BLK-xxM	REV. A
				SCALE: NONE		CAD FILE: TRD815SRA6BLK-xxM.SLDRW	SHEET 1 OF 1