


## REVISION

ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	08/01/2025	BZHANG	WLI



## NOTES

**MATERIAL:**  
MOLDED HOOD: PVC, BLACK, UV RESISTANCE  
M12 INSULATOR: NYLON, BLACK  
M12 SHELL/SCREW NUT: BRASS, NICKEL PLATED  
M12 CONTACTS: PHOSPHOR BRONZE, 15 $\mu$ " MIN. GOLD PLATED

**ELECTRICAL:**  
NOMINAL VOLTAGE RATING: 250 VAC/VDC  
MAX CURRENT: 4A


**APPLICATION:**  
INGRESS PROTECTION RATING IS IP67 (MATED).

**ENVIRONMENTAL:**  
OPERATING TEMPERATURE RANGE: -40°C TO +75°C  
CABLE JACKET: OIL, SUNLIGHT and WELD SPLATTER RESISTANT  
CABLE FLEX LIFE: 1 MILLION CYCLE TEST (10X CABLE OD)  
10 MILLION CYCLE TEST (20X CABLE OD)

**MISCELLANEOUS**  
CABLE ASSEMBLIES TO BE TESTED FOR CONTINUITY  
CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN  
ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

**REGULATORY COMPLIANCE:**  
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



PART NUMBER	LENGTH	
	METERS	FEET
TRG507-C4T-05M	0.5	1.64
TRG507-C4T-1M	1.0	3.28
TRG507-C4T-2M	2.0	6.56
TRG507-C4T-3M	3.0	9.84
TRG507-C4T-5M	5.0	16.41
TRG507-C4T-10M	10.0	32.82
TRG507-C4T-15M	15.0	49.22

UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

**TOLERANCES:**  
X =  $\pm .2$  [5]  
XX =  $\pm .02$  [0.5]  
XXX =  $\pm .005$  [0.13]  
FRACTIONS  
 $\pm 1/32$   
ANGLES  $\pm 1^\circ$

**CABLE LENGTH TOLERANCES:**  
≤12 [305] =  $\pm 1$  [25] / -0  
≥12 [305] ≤ 60 [1524] =  $\pm 2$  [51] / -0  
≥60 [1524] ≤ 120 [3048] =  $\pm 4$  [102] / -0  
≥120 [3048] ≤ 300 [7620] =  $\pm 6$  [152] / -0  
≥300 [7620] =  $\pm 5\%$  / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY  
AND SUBJECT TO CHANGE WITHOUT NOTICE  
UN-DIMENSIONED/NON-CRITICAL FEATURES  
MAY VARY IN SIZE AND LOCATION  
COLORS MAY VARY

**L-COM**  
an INFINITE<sup>®</sup> brand

Website: [www.L-com.com](http://www.L-com.com)  
Phone: 1.800.341.5266 | 1.978.682.6936



INTERPRET ALL DIMENSIONS AND  
TOLERANCES PER ASME Y14.5

SCALE SHEET  
NONE 1 OF 1

DESCRIPTION C5E M12D RA M/M PVC 24 TEL

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	43321	BZHANG	TRG507-C4T	A