

1. CONSTRUCTION:

1. CONDUCTOR: STRANDED PLAIN ANNEALED BARE COPPER WIRE 7/0.250±0.008mm (22AWG)
2. INSULATION: FOAM-PE, 1.75±0.05mm
3. TWISTING: 1 TWISTED PAIR, 2 SINGLE CONDUCTORS PAIRED,
TWISTED PAIR COLOR CODE: WHITE/BLUE
4. SHIELDING (1): ALUMINUM / MYLAR TAPE, WRAPPED ALUMINUM SIDE FACE-OUT.
5. SHIELDING (2): TINNED COPPER WIRE BRAIDING, MIN. 85% COVERAGE.
6. OUTER DIAMETER: 5.3±0.3 mm
7. JACKET COLOR: RAL 6018 GREEN

2. MECHANICAL PROPERTIES:

1. BEND RADIUS: ≥4X OD WITHOUT LOAD, ≥8X OD WITH LOAD
2. TEMPERATURE RANGE:
DURING OPERATION: -40°C UP TO 80°C
DURING INSTALLATION: 0°C UP TO 50°C
3. FIRE RATING:
MATERIAL: PUR
FIRE RATING: IEC 60332-1
4. OIL RESISTANCE TO UL 758 60°C
5. UV RESISTANCE TO IEC 60068-2-5

MECHANICAL PROPERTIES	TESTING METHOD	SPECIFICATION
TENSILE INITIAL	UL 1581	MIN 10.3 Mpa
ELONGATION INITIAL		MIN 100%
HEAT AGING (TENSILE)		MIN 70% OF UNAGED SPECIMENS
HEAT AGING (ELONGATION)		MIN 65% OF UNAGED SPECIMENS
HYDROLYSIS (TENSILE)	VDE HD 22.10	±30% OF UNHYDROLYZED SPECIMENS
HYDROLYSIS (ELONGATION)		MIN 300% ±30% OF UNHYDROLYZED SPECIMENS

3. REFERENCE STANDARD: IEC 61156-12

4. ELECTRICAL PROPERTIES (AT 20°C ±5°C)

1. DC RESISTANCE: MAX 14.5Ω /100m AT 20°C
2. RESISTANCE UNBALANCE: MAX 2% AT 20°C
3. INSULATION RESISTANCE (500V): MIN 5000 MΩ/Km AT 20°C
4. MUTUAL CAPACITANCE: MAX 5.6nf/100m AT 1kHz
5. CAPACITANCE UNBALANCE (PAIR TO GROUND): MAX 160pf/100m AT 1kHz
6. NOMINAL VELOCITY OF PROPAGATION: NOM 67%
7. TEST VOLTAGE (AC, 1 min): 2kV/1min
8. COUPLING ATTENUATION: TYPE I


5. TRANSMISSION PERFORMANCE ACC. TO IEC 61156-12 (AT 20°C/100m):

FREQUENCY (MHz)	IMPEDANCE (Ω)	INSERTION LOSS (dB) MAX	RETURN LOSS (dB) MIN	PROPAGATION DELAY (ns) MAX
1	100±15	3.1	20.0	570
4		5.6	23.0	552
10		8.7	25.0	545
16		11.0	25.0	543
20		12.2	25.0	542
31.25		15.5	23.2	541
62.5	100±22	21.8	20.8	538
100		27.8	19.0	538
125		31.2	18.2	537
200		39.7	16.4	537
250		44.6	15.6	536
300		49.0	15.6	536
500	100±25	64.1	15.6	536
600		70.7	15.6	536

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

REVISION

ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	02/17/2025	HBAKKE	GUTTADAURO

CROSS-SECTIONAL
VIEW

CABLE LENGTH

PART NO.	FEET	METERS
TSPE05-10M	32.8	10
TSPE05-50M	164.0	50

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS


TOLERANCES:
X = ±.2 [5] FRACTIONS
.XX = ±.02 [0.5] ± 1/32
.XXX = ±.005 [0.13] ANGLES ± 1°

CABLE LENGTH TOLERANCES:
≤12 [305] = +1 [25] / -0
>12 [305] ≤ 60 [1524] = +2 [51] / -0
>60 [1524] ≤ 120 [3048] = +4 [102] / -0
>120 [3048] ≤ 300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY
AND SUBJECT TO CHANGE WITHOUT NOTICE.
UN-DIMENSIONED/NON-CRITICAL FEATURES
MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY

L-com
an INFINIT® brand

Website: www.L-com.com
Phone: 1.800.341.5266 | 1.978.682.6936



INTERPRET ALL DIMENSIONS AND
TOLERANCES PER ASME Y14.5

SCALE SHEET
NONE 1 OF 1

DESCRIPTION

SINGLE PAIR ETHERNET (SPE) BULK CABLE, 22AWG
STRANDED, NO FILLER 5.3mm, DOUBLE SHIELDED, SF/TP,
INDUSTRIAL OUTDOOR, PUR GREEN

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	43321	HBAKKE	TSPE05	A