

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP66 NEMA 4 Enclosure, Modified Base Drilled Mount Gray

NB141207-01

Features

- Molded Fiberglass Reinforced Polyester (FRP) industrial enclosure
- · Stainless steel quick release latches with padlock hasps

Applications

- · Remote wireless LAN WiFi equipment installations
- · Indoor and outdoor installations
- · Rapid deployment installations

- NEMA Type 4 / IP66 rated*
- · Fully gasketed raised lid & integral mounting flange
- · Includes drilled aluminum mounting plate with AC socket cutouts
- · Corrosive environments & hotspot
- · Protection of equipment from theft or damage

Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded fiberglass reinforced polyester, it is well suited for high temperature or corrosive environments. The integrated mounting flange allows it to be mounted directly to any flat wall surface provided proper screws are used into secure studs. The enclosure can also be mounted to a wide diameter range of poles with one of our optional pole mounting hardware kits. The raised lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. Includes fully gasketed lid & integral mounting flange. The enclosure material is UV stabilized and comes in machine tool gray.

Mounting Plate

The modified aluminum mounting plate included with the NB141207-01 comes with pre-drilled and cut holes to use as needed to mount WLAN equipment or whatever equipment you may require. The enclosure also features holes for two N-Bulkhead lightning protectors or connectors, a grounding lug, and a cable conduit connector.

The HGX-PMT series of pole mounting kits allow the populated enclosure to be securely mounted to a variety of different size poles.

Compatible versions include HGX-PMT13, HGX-PMT16, HGX-PMT28, HGX-PMT29, HGX-PMT30 & HGX-PMT33

*Note: Enclosure ports (cable conduit connector and N-type holes for lightning protectors or connectors) must be properly sealed to maintain NEMA Type 4 / IP66 rating

Mechanical Specifications

OILO
Outer Height
Outer Width
Outer Depth
Inner Height
Inner Width Inner
Depth

Weight

Enclosure Material

15.5 in [393.7 mm] 13.32 in [338.33 mm] 8.26 in [209.8 mm] 14 in [355.6 mm] 12 in [304.8 mm] 7.95 in [201.93 mm] 10.6 lbs [4.81 kg]

Fiberglass Reinforced Polyester (FRP)

Environmental Specifications

NEMA Rating Ingress Protection (IP) Rating Temperature Continuous

IP66 -50 to +150°C



14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP66 NEMA 4 Enclosure, Modified Base Drilled Mount Gray

NB141207-01

Compliance Certifications

UL Listed

No

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP66 NEMA 4 Enclosure, Modified Base Drilled Mount Gray from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning

and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

URL: https://www.l-com.com/nema-enclosures-14x12x7-inch-weatherproof-nema-3r-enclosure-with-drilled-mounting-plate-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

NB141207-01 CAD Drawing

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP66 NEMA 4 Enclosure, Modified Base Drilled Mount Gray

