

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof
Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT
PLT, Thermostat Heat & 85F Turn on Fan Gray



NB141207-1HF-1

Features

- Molded Fiberglass Reinforced Polyester (FRP) enclosure with integral mounting flanges
- Fully gasketed lid with stainless steel quick release latches with padlock hasps
- NEMA Type 3R / IP24 rated
- Aluminum mounting plate with surge protected duplex 120 VAC outlets
- Thermostat controlled heating and cooling system

Applications

- Remote wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Rapid deployment installations
- Corrosive environments & hotspot
- Security and surveillance equipment installations

Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded fiberglass reinforced polyester, it is well suited for high temperature or corrosive environments. The integrated mounting flange allows it to be mounted directly to any flat wall surface provided proper screws are used into secure studs.

The enclosure can also be mounted to a wide diameter range of poles with one of our optional pole mounting hardware kits.

The raised lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. Includes fully gasketed vented lid with filters & integral mounting flange.

Mounting Plate

The aluminum mounting plate included with the NB141207-1HF-1 features standard surge protected duplex 120 VAC outlets and a terminal block for easy hook up to externally provided line power. The enclosure also features holes for two N-Bulkhead Lightning Protectors or Connectors, a grounding lug and cable conduit connector.

Heating & Cooling

To help ensure trouble-free operation of electronic equipment, proper operating temperatures inside an enclosure need to be controlled. With the built-in heater and cooling fan, internal temperatures can be better maintained. This model is ideal in Hot and/or Cold environments.


For Heating the NB141207-1HF-1 includes a thermostat-controlled 200W heater. The heater turns on when the internal temperature drops to 40° F (4° C) ±7° and turns off at 60° F (15° C) ±5°. The heater does not require the use of any of the AC outlets, leaving them all available for your equipment. No extra room for the heater is required since it is mounted underneath the plate.

For Cooling the NB141207-1HF-1 model includes a thermostat-controlled 16.4W fan. The high airflow, low noise fan used allows warm air to be actively pushed out the top vent while the lower vent passively pulls in outside air into the enclosure. Filters for both ports prevent foreign objects or debris from entering the enclosure. The fan turns on when the internal temperature rises to 85° F (29° C) ±5° and turns off at 67° F (29° C) ±5°. Like the heater, the cooling fan does not require the use of any of the AC outlets, leaving them all available for your equipment.

The HGX-PMT series of pole mounting kits allow the populated enclosure to be securely mounted to a variety of different size poles.

Compatible versions include HGX-PMT13, HGX-PMT16, HGX-PMT28, HGX-PMT29, HGX-PMT30 & HGX-PMT33

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof
Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT
PLT, Thermostat Heat & 85F Turn on Fan Gray



NB141207-1HF-1

Mechanical Specifications

Size

| | | |
|--------------------|---------------------------------------|-------------|
| Outer Height | 15.5 in | [393.7 mm] |
| Outer Width | 13.32 in | [338.33 mm] |
| Outer Depth | 8.26 in | [209.8 mm] |
| Inner Height | 14 in | [355.6 mm] |
| Inner Width Inner | 12 in | [304.8 mm] |
| Depth | 7.95 in | [201.93 mm] |
| Weight | 12.5 lbs | [5.67 kg] |
| Enclosure Material | Fiberglass Reinforced Polyester (FRP) | |

Environmental Specifications

| | |
|--------------------------------|---------------|
| NEMA Rating | 3R |
| Ingress Protection (IP) Rating | IP24 |
| Temperature Continuous | -50 to +150°C |

Compliance Certifications

| | |
|-----------|----|
| UL Listed | No |
|-----------|----|

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT, Thermostat Heat & 85F Turn on Fan Gray from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

URL: <https://www.l-com.com/nema-enclosures-14x12x7-inch-120-vac-weatherproof-enclosure-with-heater-and-85-degree-turn-on-cooling-fan-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

NB141207-1HF-1 CAD Drawing

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT, Thermostat Heat & 85F Turn on Fan Gray

