

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 240 VAC MNT PLT, Mechanical Thermostat Fan Gray



NB141207-20F

Features

- Molded Fiberglass Reinforced Polyester (FRP) industrial enclosure
- Stainless steel quick release latches with padlock hasps
- NEMA Type 3R / IP24 rated

Applications

- · Remote wireless LAN WiFi equipment installations
- · Indoor and outdoor installations
- · Hot temperature environments

- Fully gasketed raised vented lid with filters & integral mounting flange
- Features aluminum mounting plate with 240 VAC terminal strip & thermostat controlled cooling system
- · Corrosive environments & hotspot
- · Protection of equipment from theft or damage

Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded fiberglass reinforced polyester, it is well suited for high temperature or corrosive environments. The integrated mounting flange allows it to be mounted directly to any flat wall surface provided proper screws are used into secure studs.

The enclosure can be also be mounted to a wide diameter range of poles with one of our optional pole mounting hardware kits.

The raised lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. Includes fully gasketed vented lid with filters & integral mounting flange. The enclosure material is UV stabilized and comes in machine tool gray.

Mounting Plate

The modified aluminum mounting plate included with the NB141207-20F comes pre-drilled and cut holes and a 240VAC terminal block for easy

hook up to externally provided line power to use as needed to mount WLAN equipment or whatever equipment you may require. The enclosure also features holes for two N-Bulkhead lightning protectors or connectors, a grounding lug, and a cable conduit connector.

Cooling

To help ensure trouble-free operation of electronic equipment, proper operating temperatures inside an enclosure need to be controlled.

With the built-in cooling fan, internal temperatures can be better maintained. This model is ideal in hot environments.

For cooling the NB141207-20F model includes a thermostat-controlled 18W fan. The high airflow, low noise fan used

allows warm air to be actively pushed out the top vent while the lower vent passively pulls in outside air into the enclosure. Filters for both ports prevent foreign objects or debris from entering the enclosure. The fan turns on when the internal temperature rises to 120° F (49° C) $\pm 5^{\circ}$ and turns off at 90° F (32° C) $\pm 10^{\circ}$.

The HGX-PMT series of pole mounting kits allow the populated enclosure to be securely mounted to a variety of different size poles.

Compatible versions include HGX-PMT13, HGX-PMT16, HGX-PMT28, HGX-PMT29, HGX-PMT30 & HGX-PMT33

Mechanical Specifications

Size		
Outer Height	15.5 in	[393.7 mm]
Outer Width	13.32 in	[338.33 mm]
Outer Depth	8.26 in	[209.8 mm]
Inner Height	14 in	[355.6 mm]
Inner Width Inner	12 in	[304.8 mm]
Depth	7.95 in	[201.93 mm]
Weight	10.81 lbs	[4.9 kg]
Enclosure Material	Fiberglass Reinforced Polyester (FRP)	



14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 240 VAC MNT PLT, Mechanical Thermostat Fan Gray



NB141207-20F

Environmental Specifications

NEMA Rating Ingress Protection (IP) Rating Temperature Continuous

-50 to +150°C

Compliance Certifications

UL Listed

No

3R IP24

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 240 VAC MNT PLT, Mechanical Thermostat Fan Gray from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as

 $well \ as \ lightning \ and \ surge \ protectors, \ NEMA \ rated \ enclosures, \ and \ an \ RF \ product \ line \ which \ includes \ antennas, \ amplifiers, \ passive, \ and \ active \ components.$

URL: https://www.l-com.com/nema-enclosures-14x12x7-inch-240-vac-weatherproof-enclosure-with-cooling-fan-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

NB141207-20F CAD Drawing

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 240 VAC MNT PLT, Mechanical Thermostat Fan Gray

