

RF PCB Connector, SMA, Male, Up to 6 GHz, End Launch, Straight, 0.062 inch PCB Thickness



RFPCB-SMA-MS6G-37

Configuration

- SMA Male Connector
- 50 Ohms
- Straight Body Geometry
- End Launch Interface Type
- Solder Attachment

Features

- Max. Operating Frequency 6 GHz
- Good VSWR of 1.07:1
- Gold Plated Brass Contact

Applications

- General Purpose Test
- PCB Applications

Description

RFPCB-SMA-MS6G-37 SMA male PCB connector available from L-com has a 50 Ohm impedance. This RF connector has an end launch connector mount interface and is designed for a wide variety of Printed-Circuit Board (PCB) applications in RF and microwave systems. This SMA male connector uses solder as an attachment method. Our SMA male PCB connector provides a minimum frequency of DC and a maximum frequency of 18GHz. The SMA connector is available in a 0.71-inch length and 0.49-inch width. The L-com SMA male PCB connector has a PTFE dielectric type and a VSWR of 1.07:1. This SMA PCB connector has a brass body with gold plating. RFPCB-SMA-MS6G-37 SMA connector uses brass contacts and gold plating material. This SMA male PCB radio frequency connector is RoHS and REACH compliant.

This L-com SMA male connector will ship the same day as purchased. Our SMA male connector is part of over 40,000 RF, microwave, and millimeter wave components in stock for worldwide shipment. We also build SMA custom connector cable assemblies that will ship the same day as well.

The SMA male connector with 50 Ohm impedance has a weight of 0.0084 lbs. This RF connector has a high-quality construction. The male coaxial connector is capable of operating at temperatures ranging from -65 deg C to 165 deg C. We currently have a variety of antenna, audio/video, Ethernet, fiber optic, and USB connectors in our portfolio that are ready to ship today. For further information on similar products, our expert technical support and knowledgeable sales team can help you get the high-quality RF that meets your requirements.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.07:1	
Operating Voltage (AC)			1,000	Vrms

Mechanical Specifications

Size

Length	0.71 in [18.03 mm]
Width	0.49 in [12.45 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [RF PCB Connector, SMA, Male, Up to 6 GHz, End Launch, Straight, 0.062 inch PCB Thickness RFPCB-SMA-MS6G-37](#)

RF PCB Connector, SMA, Male, Up to 6 GHz, End Launch, Straight, 0.062 inch PCB Thickness



RFPCB-SMA-MS6G-37

Height	0.49 in [12.45 mm]
Weight	0.01 lbs [3.81 g]
Mating Cycles	200 Cycles

Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Gold
Coupling Nut	Brass	Gold
Retaining Ring	Beryllium Copper	Nickel

Environmental Specifications

Temperature	
Operating Range	-65deg C to +165deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

RF PCB Connector, SMA, Male, Up to 6 GHz, End Launch, Straight, 0.062 inch PCB Thickness from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RF PCB Connector, SMA, Male, Up to 6 GHz, End Launch, Straight, 0.062 inch PCB Thickness RFPCB-SMA-MS6G-37

URL: <https://www.l-com.com/rf-pcb-connector-sma-male-up-6-ghz-end-launch-straight-rfpcb-sma-ms6g-37-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

