

IP66/67 Single Mode Fiber Industrial Duplex LC Outlet

XLC-SM

Configuration

Connector 1	ODVA-LC Female
Connector 2	LC
Adapter Design	Mil/Industrial
Body Style	Straight
Mount Method	Circular Panel Mount
Simplex/Duplex	Duplex
Mode	Single Mode

Mechanical Specifications

Temperature	
Operating Range, deg C	-40 to +85
Size	
Length, in [mm]	1.25 [31.75]
Width/Dia., in [mm]	1.3 [33.02]
Height, in [mm]	1.3 [33.02]
Color	Black

Connector 1	
Type	ODVA-LC Female
Mating Cycles	500
Body Material and Plating	PBT

Connector 2	
Type	LC

Compliance Certifications

RoHS Compliant

Plotted and Other Data

- Notes:
- Values at +25 °C, sea level

IP66/67 Single Mode Fiber Industrial Duplex LC Outlet from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

URL: <https://www.l-com.com/fiber-optic-ip66-67-single-mode-fiber-industrial-duplex-lc-outlet>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

XLC-SM CAD Drawing
IP66/67 Single Mode Fiber Industrial Duplex LC Outlet

